

TUNING FORK CYLINDRICAL CRYSTAL (2.0 x 6.2mm)

FEATURES:


- MINIATURE TUNING FORK CRYSTAL
- EXCELLENT HEAT RESISTANCE



■ SPECIFICATION


FREQUENCY RANGE	STD: 32.768kHz (30kHz ~ 360kHz available)
FREQUENCY TOLERANCE @ 25°C	±20ppm
TEMPERATURE COEFFICIENT	-0.034ppm ±0.006ppm / °C ² typ.
OPERATING TEMPERATURE RANGE	-20°C ~ 70°C
STORAGE TEMPERATURE RANGE	-55°C ~ 125°C
TURN OVER TEMPERATURE	25°C ± 5°C
LOAD CAPACITANCE	STD: 12.5pF (See P/N guide for other options)
SHUNT CAPACITANCE	1.35pF typ.
MOTIONAL CAPACITANCE	0.003pF typ.
CAPACITANCE RATIO	460 typ.
EQUIVALENT SERIES RESISTANCE	40kΩ max.
INSULATION RESISTANCE	500MΩ min. @ 100V _{DC} ±15V _{DC}
DRIVE LEVEL	1.0μW max.
AGING @ 25°C ± 3°C	±5.0ppm / 1 st year max.

■ PACKAGE DIMENSIONS




Unit:mm

■ TEMPERATURE COEFFICIENT



■ PART NUMBERING GUIDE



Transko Electronics, Inc reserves the right to make changes to the product (s), service (s), and specification (s) described herein without notice. See "Terms of Sale" for details on our website.